



BRM GLOBAL

General Features

Two-Way Emergency
Communication Systems in
Eligible for 81-28 Standard



BRM GLOBAL

GENERAL FEATURES

Brm Series Products are fully comply En 81.28:2019+AC, EN 81.70, EN 81.71, EN 81.72 standards. Also, it has P100 protocol. It can works with 2G or 4G technology.

01

Filtering

Brm products with advanced filtering function, it is filters the fails, do not make busy the communication centers and emergency staff with redudant alarms.

02

Responsibility

Brm devices diagnosys battery status automatically. Al, warns to the maintanence company and control center when battery level %50 and %30 .

03

Adjustable Volume Level

According to related standarts, adjustable volume level between 35dB – 65Db.

04

Automatic Self Test

Device automatically test itself within every 72hours. To be active this feature, an active simcard should be in the device. for sms or data sending,a master gsm number provided by authorised person or Brm Cloud services should be setted for test procedure.

05

Ethics

Brm main control unit charges and checks of status of emergency batteries that plugged to the device.

06

Induction Loop

It has the feature of direct connection from BRM Products to induction loop devices that are used to amplify the sound for the hearing impaired persons





07

Disability compliance

Brm products have a light system that meets the requirements of En 81.70 and optionally relay outputs that can be connected to buttons.

08

Handsfree button

BRM products are equipped with handsfree emergency alarm buttons as shown in the 81 / 20-50 standard.

09

Easy Installation

Brm Series products easy assembly with detailed assembly schemes.

10

Technical Support

Face to face trainings and 7/24 technical support service at your disposal.

11

Internal Intercom

BRM products have an internal intercom feature that enables the communication of the machine room with the inside of the cabin and the elevator shaft in cases where the shaft distance is over 30m and elevators without machine room.

12

Advanced Software

Brm Devices monitored via brm cloud system. Maintenance team, elevator malfunctions and maintenance can track online. With the can bus protocol, you can track all the malfunctions in the elevators if you have complied contracted control panel.

13

Compatibility

Brm Devices are complied with all control panels.

14

Price advantage

Brm Devices are Works with all simcard operators.

15

Package of Device

Brm Devices has packed with; Cabin, Pit and Over Cabin modules

OTHER BRM PRODUCTS



BRM 630 D 4G



VOIP 721



BRM 630 4G



TFT SCREEN



ALARM BUTTON



INTERCOM

CONTACT INFORMATION

Address

Ostim OSB Mahallesi Alinteri Bulv. No:29/36
Yenimahalle / Ankara / Turkey

Phone

+90 312 386 17 80

Technical Support

+90 555 109 57 40

Email

marketing@brmelektronik.com
brm@brmelektronik.com

Website

www.brmelektronik.net